



21600 NORDHOFF ST.
CHATSWORTH, CALIFORNIA 91311 USA
PH: (818) 882-1238 FAX: (818) 882-7144
E-Mail: sor@sor.com
Internet: <http://www.sor.com>

#309-4511-RHD FRONT TUFF DUCK SLIP COVER

FITS 1975-1978 FJ45 PICK UP RHD

PLEASE READ INSTRUCTIONS BEFORE INSTALLATION

Warm up slip covers in the sun till they are soft and warm before installation. Or you can put slip cover inside pillow case and put in clothes dryer for a few minutes. Be careful to close slip cover so the slip covers do not come in contact with the dryer drum, other wise you will melt the backing on this slip cover.

Be sure the hook and loop strips sewn along the sides of the cushions are separated. When properly installed.

INSTALLATION INSTRUCTIONS

Driver and Passenger Backrest

- STEP 1. Position the covers over each backrest. Note, the hook strip (rough surface) should be at the back and the loop strip (soft surface) should be facing you at the bottom of the cover. You might have to squeeze the backrest slightly to get the cover over the top and bottom corners. Fold the hook and loop flaps around the bottom of the backrest, and securely mate together.
- STEP 2. Position the drivers side cover over the cushion. Align the strap on each side around the back of the metal support bracket and mate with the loop strip sewn on the flap.
- STEP 3. Position the long strap on the front, bottom of the cushion UNDER the seat and mate the hook strip on the strap with the loop strip on the flap.
- STEP 4. Position the passenger cover over the cushion. Align the strap on each side around the back of the metal support bracket and mate with the loop strip sewn on the flap.
- STEP 5. Position the two loop strips on the front, bottom of the cushion AROUND the metal supports and mate to the hook strips on the cover.

CARE INSTRUCTIONS

Cold water wash, line dry. May be dry cleaned, no trichlorethylene.

NOTE: If covers are left in direct sunlight for extended periods of time covers will tend to fade.